



The
Patent
Office

PCT/GB 00 / 0 1 5 8 2

10/01 8330

INVESTOR IN PEOPLE

REC'D 15 MAY 2000

WIPO PCT
The Patent Office

Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

25/

PRIORITY DOCUMENT
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH
RULE 17.1(a) OR (b)

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

GB 00 / 01582

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

R. Mahoney

Dated

18th April 2000

THIS PAGE BLANK (USPTO)

Patents Act 1977

16)

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference SEM/MSAK/52691/0000

2. Patent
(The Pa

9909468.2

23 APR 1999

3. Full name, address and postcode of the or of each applicant (underline all surnames)

ELLIOTT INDUSTRIES LIMITED
ELLIOTT HOUSE
VICTORIA ROAD
LONDON
NW10 6NY

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

UK

5360334001

4. Title of the invention

IMPROVEMENTS IN OR RELATING TO ABRASIVE FLAP DISCS

5. Name of your agent (if you have one)

BOULT WADE TENNANT
27 FURNIVAL STREET
LONDON
EC4A 1PQ

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

42001

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant

of a patent required in support of this request?

YES

(Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
- b) there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body.

See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 12

Claim(s) 4

Abstract

Drawing(s) 3 + 3



10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) 1 ✓

Request for substantive examination (Patents Form 10/77)

Any other documents (Please specify)

11

I/We request the grant of a patent on the basis of this application.

Signature

Date



23 April 1999

12. Name and daytime telephone number of person to contact in the United Kingdom

Dr. Saiful Khan
0171 430 7500

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

IMPROVEMENTS IN OR RELATING TO ABRASIVE FLAP DISCS

The invention relates to abrasive flap discs which are used for a variety of finishing, grinding
5 and polishing operations, particularly on welded fabrications.

Generally, flap discs comprise a relatively stiff backing plate onto which abrasive flaps are adhered.
10 The backing plate can be angled, flat, depressed, raised, or a combination of these variations. They are typically 4"-9" (10.16cm-22.86cm) in diameter, although smaller diameter discs are being introduced. The abrasives used are ordinarily 24-120 grit.

15 There are alternatives to flap discs, such as Depressed Centre (resin bonded) Grinding Wheels (DCGWs). However, these are only suitable for removing large amounts of material and generally can
20 not provide suitable finishing. Thus, the use of Sanding Discs (SDs) is required subsequent to the grinding operation. Unlike these two aforementioned counterparts, flap discs are multi-purpose, this being partly attributable to the fact that the surface
25 operation performed by them is somewhat dependent upon the pressure applied by the operator.

Furthermore, the superior properties of flap discs over DCGWs are attributable to the fact that
30 flap discs use coated abrasives (unlike bonded abrasives for a DCGW), which inherently present the majority of the abrasive grit particles at their optimum cutting attitude whilst providing a potentially "softer" operation, removing material at a
35 variable rate dependent upon the pressure applied and

contributing to an improved surface finish. Flap discs are also considered superior to SDs due to the use of multi-layer coated abrasives, which provide a substantially greater amount of useable abrasive cloth, in the region of 20:1, to provide a substantially longer life for the flap discs.

Although flap discs are "softer" than DCGWs, flap discs are still "hard", particularly when finer grit sizes are used, and as such do not lend themselves to contouring or blending work. There have been moves to develop flap discs which are "softer", but these have concentrated on providing a backing plate with reduced stiffness, e.g. Zircotex (RTM). In such cases, this has not been wholly successful as the necessary combination of a "flexible" disc and "support pad" have proved to be too rigid. Thus, the operational range of these flap discs are significantly limited. Moreover, the configuration of flap discs prevents them from being capable of dressing sharp corners.

The present invention provides an abrasive flap disc comprising a backing plate, an annular array of flaps of abrasive material arranged on the backing plate and bonded thereto along the lowermost edge of each flap, wherein each flap, at least in a radially outer region, is substantially spaced from each adjacent flap such that the flaps have freedom to flex and conform to an underlying surface in use.

30

Preferably, each flap does not contact an adjacent flap at all. Alternatively, each flap contacts an adjacent flap along its radially inner edge.

35

Preferably, the angle between the backing plate and each flap is in the range of approximately 20° to approximately 90°. Advantageously, the angle between the backing plate and each flap is in the range of approximately 40° to approximately 70°.

10 In one embodiment, the abrasive flaps of the disc may be arranged such that a centerline of each flap, which extends between its radially inner and outer edges, is substantially on a radius of the backing plate.

Alternatively, the centerline of each flap may be at an angle to a radius of the backing plate.

15 Advantageously, the angle between each flap centerline and a radius of the backing plate is in the range of approximately between 5° to approximately 85°. Most preferably, the angle between each flap centerline and a radius of the backing plate is in the range of

20 approximately between 30° to approximately 60°.

Preferably, the flaps comprise abrasive grit bonded to a backing material and the backing plate includes means to attach the disc to a drive

25 mechanism.

The invention further provides a method of producing an abrasive flap disc of the type described above, comprising the steps of providing a backing

30 plate; providing an adhesive on an upper surface of the backing plate; rotating the backing plate incrementally; at each incremental step, feeding the end of a strip of abrasive material on to the adhesive on the backing plate; severing the end of the strip to

35 form a flap; repeating the process until an annular

array of flaps is formed on the backing plate with each flap, at least in a radially outer region, being spaced from each adjacent flap; maintaining the flaps in the spaced position; and curing the adhesive to
5 secure the flaps to the backing plate.

Preferably, after constructing the array of flaps and before curing, the method further includes the step of placing the disc in a former adapted to
10 prevent each flap falling into substantial contact with an adjacent flap.

The former may include a cylindrical wall dimensioned to encircle the disc and prevent each flap
15 falling into substantial contact with an adjacent flap. Alternatively, a spoke-shaped frame may be placed with a spoke positioned between adjacent flaps to prevent each flap falling into substantial contact with an adjacent flap.

20 In one embodiment, the strip of abrasive material is fed such that each flap has a centerline extending from its radially inner to outer edge which is substantially on a centerline of the backing plate.

25 Alternatively, the strip of abrasive material may be fed such that each flap has a centerline extending from its radially inner to outer edge which is at an angle to a radius of the backing plate.

30 The invention therefore provides flap discs having an arrangement of abrasive flaps which give the flaps pliability and increased freedom to flex and conform to an underlying surface, thereby increasing
35 the applicability of flap discs whilst maintaining

sufficient support for the abrasive flaps such that the operational range of the abrasive flap discs is also maintained. Specifically, the flap disc operator can use a single tool to perform a number of
5 functions, efficiently controlling the operation performed by the pressure and angle of approach applied to the tool. Moreover, the arrangement of abrasive flaps provided is still sufficiently stiff such that the grinding of particularly rough surfaces
10 is possible. In particular, the flap discs of this invention can be used in contour and blending work, and also to dress sharp corners.

It is recognised that there are other processes
15 for the manufacture of flap discs which differ in specific ways from the normal process referred to above. However the invention is valid regardless of how the cloth and flaps are presented, cut or adhered to the backing plate.

20 The invention will now be described in detail, by way of example only, with reference to the following drawings in which :

25 Figure 1 is a plan view of a typical flap disc;

Figure 2 is a side view of the flap disc of Figure 1;

30 Figure 3 is plan view of a flap disc in accordance with one embodiment of the present invention, in which the centerlines of the abrasive flaps are aligned with radii of the backing plate;

35 Figure 4 is a side view of the flap disc of

Figure 3;

Figure 5 is a plan view of a flap disc in accordance with a second embodiment of the present invention, in which the centerlines of the abrasive flaps are arranged at an angle to radii of the backing plate;

Figure 6 is a side view of the flap disc of Figure 5;

Figure 7 is a plan view of a former used in the manufacturing process of the flap disc of the present invention; and

Figure 8 is a cross sectional view through the former of Figure 7 along line X-X.

As can be seen from Figures 1 and 2, current flap discs 10 comprise a backing plate 11 around the perimeter of which are arranged abrasive flaps 12. In addition, the backing plate 11 comprises a central hole 13, which is used to locate the flap disc 10 to a drive mechanism (not shown). Of course, the hole 13 can be used to locate the flap disc 10 on any suitably sized guide pin e.g. during manufacture or storage, allowing several flap discs 10 to be stacked one upon another. The backing plate 11 may comprise a projection 40 (in addition to or instead of a hole 13) on the reverse side of the backing plate 11 to allow connection to the drive mechanism.

Although the backing plate 11 is shown to be flat in Figure 2, the backing plate 11 can be a variety of shapes including inclined from the central hole 13,

depressed or raised around the central hole 13, or some combination of these.

5 The abrasive flaps 12 themselves comprise an abrasive grit applied to a backing material such as denim. Generally, the abrasive flaps 12 are

10 rectangular in shape and are attached along one edge to the backing plate 11 using a single epoxy adhesive 14. The abrasive flaps 12 are usually cut to size from a long strip of material during manufacture of the flap disc 10.

15 Current practice is to apply the adhesive 14 onto the backing plate 11 over the region on which the abrasive flaps 12 will be positioned. The backing plate 11 is then rotated incrementally, and at each increment the end of a long strip of abrasive material is fed at an angle onto the glued region of the backing plate 11, and the end part is then cut off to

20 form a single flap. This process is repeated until the required number of flaps 12 have been applied to the backing plate 11.

25 Typically, this semi-manufactured abrasive flap disc 10 is then stacked upon another semi-manufactured abrasive flap disc 10. On occasion, a former may be used to separate the two semi-manufactured abrasive discs 10. The former is generally a disc of material which mirrors the contour of the required abrasive

30 face of the disc, and is used to apply a restraining pressure over part or the entire area over which the abrasive flaps 12 have been arranged. In particular, formers can be particularly useful when the outer face of the abrasive flaps 12 are required to be at a

35 different angle to the angle of the back face of the

backing plate 11.

5 The purpose of stacking the semi-manufactured
flaps discs 10 is to flatten each of the abrasive
flaps 12 onto one another so that the back surface of
each abrasive flap 12 rests upon the front abrasive
surface of each corresponding adjacent abrasive flap
12. Any suitable means which produce such flattened
abrasive flaps 12 can be employed e.g. not just by
10 stacking but by applying external pressure to each of
the individual flap discs 10.

15 Once flattened, the stack of abrasive discs 10 is
normally placed into an oven to cure the epoxy 14 such
that it binds the abrasive flaps 12 in the flattened
position onto the backing plates 11.

20 Current practice is to arrange the flaps 12 such
that their respective centerlines are aligned with
radii of the backing plate 11. This produces a square
hard edge which is desirable in some operations.

25 It is clear that, if a larger number of flaps 12
is to be applied to the flap disc 10, then the flaps
12 will be increasingly upright. However, the flaps
12 are always flattened as far as possible so as to
rest upon one another.

30 In contrast, flap discs 20 in accordance with two
embodiments of this invention are shown in Figures 3-
6. The flaps 12 are positioned substantially upright
such that there are significant gaps 15 between the
abrasive flaps 12. Preferably, in the abrasive flap
discs 20 of the present invention, the angle between
35 the backing plate 11 and abrasive flap 12 is between

20°-90°. More specifically, the angle between the backing plate 11 and abrasive flap 12 is between 40°-70°. With conventional flap discs, the angle of the flaps relative to the backing plate depends upon the number of flaps, as referred to above. With the flap discs of the present invention, however, the flaps are spaced from one another and hence the angle between the flaps and the backing plate is not dictated by the number of flaps.

10

Generally, each adjacent flap 12 does not rest upon its neighbour at all. However, it may be useful to arrange the flaps 12 such that adjacent flaps 12 do touch one another along their respective inner edges 16. This provides some support for the flaps 12 during curing. This contact can, of course, be line or point contact.

This relatively upright, open, arrangement of flaps 12 gives the flaps 12 increased flexibility, particularly at the outer periphery of the flap disc 20, and allows the flaps 12 to conform to an underlying surface in use. Thus, the operator is provided with the ability of aggressive, heavy cutting or light contour blending. It is therefore suitable to dress sharp corners, and can be used also for blending and contouring work.

As mentioned above, conventional flap discs 10 are manufactured with the flap centre line, which extends radially from the inner edge 16 to outer edge 17 of the flap 12, lying approximately on a diameter of the disc 10 (as best seen in Figure 1). In the first embodiment of the present invention, shown in Figures 3 and 4, the flaps 12 are also positioned in

this way.

Alternatively, in a second embodiment, shown in Figures 5 and 6, the flaps 12 are displaced such that
5 the flap centre line lies at an angle to a radius of the disc. This helps to provide an arrangement of self supporting flaps in which the inner edge 16 of each flap rests on its neighbour. Thus, the flaps 12 of this arrangement can be cured without the need for
10 a former (described below) to hold the flaps 12 up. Preferably, in the abrasive flap discs 20 of the current invention, the angle between the flap centerline and the radius of the backing plate is between 5°-85°. More specifically, the angle between
15 the flap centerline and the radius of the backing plate is between 30°-60°. This feature of the invention provides an additional benefit to the product, which is the resulting generation of angle γ (see Figure 6) which provides the added facility to
20 dress and blend sharp internal corners.

The flap discs 20 of the present invention may be manufactured using a similar process to that described above for conventional flap discs, except that
25 adjacent flaps 12 are not flattened onto one another. Following arrangement of the appropriate number of abrasive flaps 12 onto the backing plate 11, the flaps 12 are left in a substantially upright position, spaced from one another (except perhaps along their
30 inner edges 16). The semi-manufactured flap discs 20 may then be placed directly into ovens to cure the adhesive 14, or they may be placed in specially designed formers 30 (shown in Figures 7 and 8) to keep the abrasive flaps 12 upright and spaced apart. These
35 formers 30 also function to enable stacking of a

number of flap discs 20.

5 The formers 30 are typically made from pressed
steel or aluminium, but can be made from a variety of
different materials e.g. those materials which have
sufficient stiffness, which can be easily and cost
effectively manufactured into the required shapes,
and/or which have appropriate heat resistant and
thermal expansivity properties. A particular
10 embodiment of a former 30 is illustrated in Figures 7
and 8, and shows a former 30 having a cylindrical wall
31 dimensioned to encircle the abrasive flap discs and
support the flaps.

15 During manufacture, the projection 40 of the
backing plate 11 can be placed in the centre hole 33
of the former and thus locates the semi-manufactured
flap disc 20 within the former 30. In such a
position, contact between the former side wall 31 and
20 the outer edges 17 of the flaps 12 provides support
for flaps 12. In addition, the height of the side
wall 31 is greater than the height of the flap disc 20
and is therefore sufficient to allow stacking of a
number of semi-manufactured flap discs 20 contained
25 within their respective formers 30. It is important
that pressure must not be applied to the top edge 18
of the flaps 12 such that they become flattened. For
additional support, a substantially spoke-shaped frame
(not shown) could be appropriately positioned in the
30 former 20, with spokes protruding into the gaps 15,
between adjacent flaps 12, so as to support the flaps
12 during curing and prevent them falling back into
contact with adjacent flaps. Formers with different
configurations can be used so long as they perform the
35 above mentioned functions.

In summary, the process used to produce flap discs in accordance with this invention holds the flaps up and thus provides abrasive flaps which are substantially upright, with gaps or openings between the adjacent flaps. The flap discs of the present invention are more flexible than conventional discs, enabling them to be used in contour and blending work, and also to dress into sharp corners, and thus increases the usefulness of flap discs.

CLAIMS:

1. An abrasive flap disc comprising :
a backing plate,
5 an annular array of flaps of abrasive material
arranged on the backing plate and bonded thereto along
the lowermost edge of each flap,
wherein each flap, at least in a radially outer
region, is substantially spaced from each adjacent
10 flap such that the flaps have freedom to flex and
conform to an underlying surface in use.
2. An abrasive flap disc as claimed in claim 1,
wherein each flap does not contact an adjacent flap at
15 all.
3. An abrasive flap disc as claimed in claim 1,
wherein each flap contacts an adjacent flap along its
radially inner edge.
20
4. An abrasive flap disc as claimed in any preceding
claim, wherein the angle between the backing plate and
each flap is in the range of approximately 20° to
approximately 90°.
- 25 5. An abrasive flap disc as claimed in claim 4,
wherein the angle between the backing plate and each
flap is in the range of approximately 40° to
approximately 70°.
- 30 6. An abrasive flap disc as claimed in any preceding
claim, wherein a centerline of each flap, which
extends between its radially inner and outer edges, is
substantially on a radius of the backing plate.

7. An abrasive flap disc as claimed in claim 1 to 5, wherein the centerline of each flap, which extends between its radially inner and outer edges, is at an angle to a radius of the backing plate.

5

8. An abrasive flap disc as claimed in claim 7, wherein the angle between each flap centerline and a radius of the backing plate is in the range of approximately between 5° to approximately 85°.

10

9. An abrasive flap disc as claimed in claim 8, wherein the angle between each flap centerline and a radius of the backing plate is in the range of approximately between 30° to approximately 60°.

15

10. An abrasive flap disc as claimed in any preceding claim, wherein the flaps comprise abrasive grit bonded to a backing material.

20

11. An abrasive flap disc as claimed in any preceding claim, wherein the backing plate includes means to attach the disc to a drive mechanism.

25

12. A method of producing an abrasive flap disc of the type set out in claim 1, comprising the steps of :
providing a backing plate;
providing an adhesive on an upper surface of the backing plate;
rotating the backing plate incrementally;
at each incremental step, feeding the end of a

30

strip of abrasive material on to the adhesive on the backing plate;

35

severing the end of the strip to form a flap;
repeating the process until an annular array of flaps is formed on the backing plate with each flap,

at least in a radially outer region, being spaced from each adjacent flap;

maintaining the flaps in spaced positioned; and

5 curing the adhesive to secure the flaps to the backing plate.

10 13. A method of producing an abrasive flap disc as claimed in claim 12, wherein after constructing the array of flaps and before curing, the method further includes the step of placing the disc in a former adapted to prevent each flap falling into substantial contact with an adjacent flap.

15 14. A method of producing an abrasive flap disc as claimed in claim 13, wherein the former includes a cylindrical wall dimensioned to encircle the disc and prevent each flap falling substantial contact with an adjacent flap.

20 15. A method of producing an abrasive flap disc as claimed in claims 13 or 14, wherein a spoke-shaped frame is placed with a spoke positioned between adjacent flaps to prevent each flap falling into substantial contact with an adjacent flap.





25 16. A method of producing an abrasive flap disc as claimed in any of claims 12 to 15, comprising the step of feeding the strip of abrasive material such that each flap has a centerline extending from its radially
30 inner to outer edge which is substantially on a centerline of the backing plate.

17. A method of producing an abrasive flap disc as claimed in any of claims 12 to 15, comprising the step
35 of feeding the strip of abrasive material such that

each flap has a centerline extending from its radially inner to outer edge which is at an angle to a radius of the backing plate.

- 5 18. A abrasive flap disc substantially as
hereinbefore described and with reference to Figures 3
to 5.
-

- 10 19. A method of producing an abrasive flap disc
substantially as hereinbefore described and with
reference to Figures 3 to 7.
-



THIS PAGE BLANK (USPTO)




FIGURE 5




FIGURE 6

THIS PAGE BLANK (USPTO)




FIGURE 7




FIGURE 8

THIS PAGE BLANK (USPTO)